

P/N MS21318-28

Description

Fastener Length: 1/4", round head, MS21318 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS2131828

Minimum Qty (MOQ): 100

NSN: 5305-00-253-5618

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21318-28 Specifications

Fastener Length:	0.266 Inches Minimum And 0.334 Inches Maximum
Head Style:	Round
Head Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Height:	0.091 Inches Minimum And 0.103 Inches Maximum
Pilot Diameter:	0.112 Inches Minimum And 0.116 Inches Maximum
Pilot Length:	0.047 Inches Nominal
Features Provided:	Casehardened
Nonmachine Thread Style:	Drive Screw (type U)
Nonmachine Nominal Thread Diameter:	0.138 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Nondefinitive Spec/std Data:	U Type

How to Order

Order this drive screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS21318-28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS21318-28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS21318-28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms21318-28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms21318-28 and selecting the property of the proper