

## P/N MS21318-29

### **Description**

Fastener Length: 3/8", round head, MS21318 series screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS2131829

Minimum Qty (MOQ): 100

NSN: 5305-00-006-4743

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21318-29 Specifications

Fastener Length:	0.359 Inches Minimum And 0.391 Inches Maximum
Head Style:	Round
Head Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Height:	0.091 Inches Minimum And 0.103 Inches Maximum
Pilot Diameter:	0.112 Inches Minimum And 0.116 Inches Maximum
Pilot Length:	0.062 Inches Nominal
Features Provided:	Casehardened
Nonmachine Thread Style:	Drive Screw (type U)
Nonmachine Nominal Thread Diameter:	0.138 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Special Test Features:	Special Quality Control Testing
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Test Data Document:	81349-mil-p-23199 Specification (includes Engineering Type Bulletins, Brochures, etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Nondefinitive Spec/std Data:	U Type
Departure From Cited Designator:	Material Must Conform To Ships Parts Control Center Special Quality Control Provisions

## **How to Order**

Order this drive screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS21318-29">https://military-fasteners.com/screws/machine+screws/MS21318-29</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS21318-29">https://military-fasteners.com/screws/machine+screws/MS21318-29</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS21318-29">https://military-fasteners.com/screws/machine+screws/MS21318-29</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/ms21318-29">https://military-fasteners.com/screws/ms21318-29</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/ms21318-29">https://military-fasteners.com/screws/ms21318-29</a> and selecting the property of the proper