

Description

Fastener Length: 1/4", MS21318 series screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS213183 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-253-5605 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21318-3 Specifications

| | |
|---|---|
| Fastener Length: | 0.250 Inches Nominal |
| Head Style: | Round |
| Head Diameter: | 0.090 Inches Minimum And 0.099 Inches Maximum |
| Head Height: | 0.026 Inches Minimum And 0.034 Inches Maximum |
| Pilot Diameter: | 0.046 Inches Minimum And 0.049 Inches Maximum |
| Pilot Length: | 0.047 Inches Nominal |
| Features Provided: | Casehardened |
| Nonmachine Thread Style: | Drive Screw (type U) |
| Nonmachine Nominal Thread Diameter: | 0.073 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall |

How to Order

Order this drive screw from our inventory online by visiting <https://military-fasteners.com/screws/drive+screws/MS21318-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.