

Description

Length: 19/64", round head, drive type, MS21318 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2131835
Minimum Qty (MOQ):	100
NSN:	5305-00-951-2437
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21318-35 Specifications

Fastener Length:	0.312 Inches Nominal
Head Style:	Round
Head Diameter:	0.264 Inches Minimum And 0.285 Inches Maximum
Head Height:	0.099 Inches Minimum And 0.111 Inches Maximum
Pilot Diameter:	0.122 Inches Minimum And 0.126 Inches Maximum
Pilot Length:	0.047 Inches Nominal
Features Provided:	Casehardened
Nonmachine Thread Style:	Drive Screw (type U)
Nonmachine Nominal Thread Diameter:	0.152 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall

How to Order

Order this drive screw from our inventory online by visiting <https://military-fasteners.com/screws/drive+screws/MS21318-35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.