

Description

Length: 19/64", round head, drive type, MS21318 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2131835 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-951-2437 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21318-35 Specifications

| | |
|---|---|
| Fastener Length: | 0.312 Inches Nominal |
| Head Style: | Round |
| Head Diameter: | 0.264 Inches Minimum And 0.285 Inches Maximum |
| Head Height: | 0.099 Inches Minimum And 0.111 Inches Maximum |
| Pilot Diameter: | 0.122 Inches Minimum And 0.126 Inches Maximum |
| Pilot Length: | 0.047 Inches Nominal |
| Features Provided: | Casehardened |
| Nonmachine Thread Style: | Drive Screw (type U) |
| Nonmachine Nominal Thread Diameter: | 0.152 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall |

How to Order

Order this drive screw from our inventory online by visiting <https://military-fasteners.com/screws/drive+screws/MS21318-35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.