

## P/N MS21318-37

## **Description**

length: 0.50", round head, MS21318 series screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS2131837

Minimum Qty (MOQ): 100

NSN: 5305-00-850-5841

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS21318-37 Specifications

P1	0 F00 by the a Newster I
Fastener Length:	0.500 Inches Nominal
Head Style:	Round
Head Diameter:	0.264 Inches Minimum And 0.285 Inches Maximum
Head Height:	0.099 Inches Minimum And 0.111 Inches Maximum
Pilot Diameter:	0.122 Inches Minimum And 0.126 Inches Maximum
Pilot Length:	0.062 Inches Nominal
End Item Identification:	5895-01-514-7015, Communications Interface System (cis) (v) 2
Features Provided:	Casehardened
Nonmachine Thread Style:	Drive Screw (type U)
Nonmachine Nominal Thread Diameter:	0.152 Inches
Part Name Assigned By Controlling Agency:	Screw, Drive, Round Head, Type U, Steel, Carbon, Cadmium Plated
Special Features:	Screw Is Not Recommended For Use In Material The Thickness Of Which Is Less Than One Diameter Of The Screw
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Specification/standard Data:	80205 - Nas-21318, 25 Nov 1998 Which Replaced Ms21318, Rev A0./13/65 Professional/industrial Association Specification

## **How to Order**

Order this drive screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/drive+screws/MS21318-37">https://military-fasteners.com/screws/drive+screws/MS21318-37</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.