

Description


Fastener Length: 5/8", round head, MS21318 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2131858
Minimum Qty (MOQ):	100
NSN:	5305-00-253-5632
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21318-58 Specifications

Fastener Length:	0.625 Inches Nominal
Head Style:	Round
Head Diameter:	0.429 Inches Minimum And 0.457 Inches Maximum
Head Height:	0.155 Inches Minimum And 0.170 Inches Maximum
Pilot Diameter:	0.198 Inches Minimum And 0.202 Inches Maximum
Pilot Length:	0.078 Inches Nominal
Features Provided:	Casehardened
Nonmachine Thread Style:	Drive Screw (type U)
Nonmachine Nominal Thread Diameter:	0.239 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall

How to Order

Order this drive screw from our inventory online by visiting <https://military-fasteners.com/screws/drive+screws/MS21318-58> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.