

**Description**

length: 3/16, diameter: 0.073", round head, cadmium plated carbon steel, MS21318 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS213188
Minimum Qty (MOQ):	100
NSN:	5305-00-253-5607
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N MS21318-8 Specifications

Fastener Length:	0.188 Inches Nominal
Head Style:	Round
Head Diameter:	0.118 Inches Minimum And 0.127 Inches Maximum
Head Height:	0.041 Inches Minimum And 0.049 Inches Maximum
Pilot Diameter:	0.060 Inches Minimum And 0.063 Inches Maximum
Pilot Length:	0.047 Inches Nominal
End Item Identification:	Communications Terminal, Satellite An/gsc-39(v)1; Engine, Aircraft Tf33-p-3/5/9 (c/ec-135, B-52h); Trainer, B-1b Aircraft; Systems, Jp-5 Aviation Fuels; Airborne Mobile Dir Air Spt Ctl (2id), 02m Jul83)(an/uyq-3a); Close In Weapon System (ciws-phalanx); Engine, Aircraft Tf33-pw-102 (c135e, Ec-135h/k/p); Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Support Equipment, B-1 Aircraft; Gun, 5-in./54 Cal, Mk-54; Guided Missile Launching Sys
Features Provided:	Casehardened
Nonmachine Thread Style:	Drive Screw (type U)
Nonmachine Nominal Thread Diameter:	0.073 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall

## How to Order

Order this drive screw from our inventory online by visiting <https://military-fasteners.com/screws/drive+screws/MS21318-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.