

Description

length: 3/16, diameter: 0.073", round head, cadmium plated carbon steel, MS21318 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS213188 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-253-5607 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS21318-8 Specifications

| | |
|---|---|
| Fastener Length: | 0.188 Inches Nominal |
| Head Style: | Round |
| Head Diameter: | 0.118 Inches Minimum And 0.127 Inches Maximum |
| Head Height: | 0.041 Inches Minimum And 0.049 Inches Maximum |
| Pilot Diameter: | 0.060 Inches Minimum And 0.063 Inches Maximum |
| Pilot Length: | 0.047 Inches Nominal |
| End Item Identification: | Communications Terminal, Satellite An/gsc-39(v)1; Engine, Aircraft Tf33-p-3/5/9 (c/ec-135, B-52h); Trainer, B-1b Aircraft; Systems, Jp-5 Aviation Fuels; Airborne Mobile Dir Air Spt Ctl (2id), 02m Jul83)(an/uyq-3a); Close In Weapon System (ciws-phalanx); Engine, Aircraft Tf33-pw-102 (c135e, Ec-135h/k/p); Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Support Equipment, B-1 Aircraft; Gun, 5-in./54 Cal, Mk-54; Guided Missile Launching Sys |
| Features Provided: | Casehardened |
| Nonmachine Thread Style: | Drive Screw (type U) |
| Nonmachine Nominal Thread Diameter: | 0.073 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall |

How to Order

Order this drive screw from our inventory online by visiting <https://military-fasteners.com/screws/drive+screws/MS21318-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.