

Description

Fastener Length: 3/32", Thread: 2-56, Thread Length: 3/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21342202 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-395-4184 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS21342-202 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.084 Inches Minimum And 0.104 Inches Maximum |
| Fastener Length: | 0.084 Inches Minimum And 0.104 Inches Maximum |
| Head Style: | Headless (setscrew) |
| Spline Minor Diameter: | 0.040 Inches Minimum And 0.041 Inches Maximum |
| Spline Major Diameter: | 0.049 Inches Minimum And 0.050 Inches Maximum |
| Spline Width: | 0.010 Inches Minimum And 0.011 Inches Maximum |
| Point Style: | Flat |
| Internal Drive Style: | Six Spline |
| Nominal Thread Diameter: | 0.086 Inches |
| Thread Quantity Per Inch: | 56 |
| Hardness Rating: | 45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4032 Overall Or Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,c1 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 2 Type And 1 Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21342-202> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.