

Description

Fastener Length: 3/32", Thread: 2-56, Thread Length: 3/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21342202
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-395-4184
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21342-202 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.084 Inches Minimum And 0.104 Inches Maximum
Fastener Length:	0.084 Inches Minimum And 0.104 Inches Maximum
Head Style:	Headless (setscrew)
Spline Minor Diameter:	0.040 Inches Minimum And 0.041 Inches Maximum
Spline Major Diameter:	0.049 Inches Minimum And 0.050 Inches Maximum
Spline Width:	0.010 Inches Minimum And 0.011 Inches Maximum
Point Style:	Flat
Internal Drive Style:	Six Spline
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4032 Overall Or Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	2 Type And 1 Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21342-202> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.