

Description

Fastener Length: 3/32", Thread: 4-40, Thread Length: 3/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21342212
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-106-1118
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21342-212 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.094 Inches Nominal
Fastener Length:	0.094 Inches Nominal
Head Style:	Headless (setscrew)
Spline Minor Diameter:	0.050 Inches Minimum And 0.051 Inches Maximum
Spline Major Diameter:	0.061 Inches Minimum And 0.062 Inches Maximum
Spline Width:	0.013 Inches Minimum And 0.014 Inches Maximum
Point Style:	Flat
Internal Drive Style:	Six Spline
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,tyii,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21342-212> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.