

**Description**

Fastener Length: 3/32", Thread: 4-40, Thread Length: 3/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21342212
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-106-1118
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS21342-212 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.094 Inches Nominal
<b>Fastener Length:</b>	0.094 Inches Nominal
<b>Head Style:</b>	Headless (setscrew)
<b>Spline Minor Diameter:</b>	0.050 Inches Minimum And 0.051 Inches Maximum
<b>Spline Major Diameter:</b>	0.061 Inches Minimum And 0.062 Inches Maximum
<b>Spline Width:</b>	0.013 Inches Minimum And 0.014 Inches Maximum
<b>Point Style:</b>	Flat
<b>Internal Drive Style:</b>	Six Spline
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Hardness Rating:</b>	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,tyii,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21342-212> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.