

**Description**

outside 5/16", adapter, flareless tube to flared tube, carbon steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS219005
Minimum Qty (MOQ):	1
NSN:	4730-01-078-9932
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



## P/N MS21900-5 Specifications

<b>Thread Class:</b>	3a All Ends
<b>Maximum Operating Temp:</b>	225.0 Deg Fahrenheit Single Response
<b>Connection Style:</b>	External Seat For Gasket Seal (boss) 2nd End
<b>Connection Style:</b>	Flared W/ Gasket Seal (boss) 1st End
<b>Connection Type:</b>	Threaded External Boss All Ends
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch Single Response
<b>Nominal Thread Size:</b>	0.500 Inches All Ends
<b>Nominal Overall Length:</b>	1.281 Inches
<b>Material:</b>	Steel Comp 1137 Overall
<b>Material Document And Classification:</b>	Fed Std66 Fed Std Single Material Response Overall
<b>Media For Which Designed:</b>	Hydraulic Fluid Single Response
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty1,cl 3 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Flared And Flareless W/ Center Wrenching Facility
<b>Thread Series Designator:</b>	Unjf All Ends

## How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.