

Description

outside 5/16", adapter, flareless tube to flared tube, carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS219005
Minimum Qty (MOQ):	1
NSN:	4730-01-078-9932
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



P/N MS21900-5 Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	225.0 Deg Fahrenheit Single Response
Connection Style:	External Seat For Gasket Seal (boss) 2nd End
Connection Style:	Flared W/ Gasket Seal (boss) 1st End
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.500 Inches All Ends
Nominal Overall Length:	1.281 Inches
Material:	Steel Comp 1137 Overall
Material Document And Classification:	Fed Std66 Fed Std Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty1,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flared And Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.