

# P/N MS21900-6

Military-Fasteners.com

#### Description

outside diameter: 3/8", adapter, flareless tube to flared tube, carbon steel, MS21900 series fitting (REPLACEMENT PART IS MS21900V6P)

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS219006
Minimum Qty (MOQ):	1
NSN:	4730-00-541-1578
ECCN:	9A991
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



## P/N MS21900-6 Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	275.0 Deg Fahrenheit Single Response
End Item Identification:	11f Aircraft, Galaxy C-5
Connection Style:	External Seat For Gasket Seal (boss) 2nd End
Connection Style:	Flared W/ Gasket Seal (boss) 1st End
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.562 Inches All Ends
Criticality Code Justification:	Feat
Nominal Overall Length:	1.281 Inches
Special Features:	Weapon System Essential
Material:	Steel Comp 1137 Overall
Material Document And Classification:	Qq-a-637 Fed Spec Single Material Response Overall
Media For Which Designed:	Fluid Single Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Style Designator:	Flared And Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21900 Government Standard

### How to Order

Order this boss nipple from our inventory online by visiting <u>https://military-fasteners.com/fittings/boss+nipples/MS21900-6</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.