

## Description

outside diameter: 3/8", adapter, flareless tube to flared tube, carbon steel, MS21900 series fitting (REPLACEMENT PART IS MS21900V6P)

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS219006
Minimum Qty (MOQ):	1
NSN:	4730-00-541-1578
ECCN:	9A991
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS21900-6 Specifications

<b>Thread Class:</b>	3a All Ends
<b>Maximum Operating Temp:</b>	275.0 Deg Fahrenheit Single Response
<b>End Item Identification:</b>	11f Aircraft, Galaxy C-5
<b>Connection Style:</b>	External Seat For Gasket Seal (boss) 2nd End
<b>Connection Style:</b>	Flared W/ Gasket Seal (boss) 1st End
<b>Connection Type:</b>	Threaded External Boss All Ends
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch Single Response
<b>Nominal Thread Size:</b>	0.562 Inches All Ends
<b>Criticality Code Justification:</b>	Feat
<b>Nominal Overall Length:</b>	1.281 Inches
<b>Special Features:</b>	Weapon System Essential
<b>Material:</b>	Steel Comp 1137 Overall
<b>Material Document And Classification:</b>	Qq-a-637 Fed Spec Single Material Response Overall
<b>Media For Which Designed:</b>	Fluid Single Response
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Flared And Flareless W/ Center Wrenching Facility
<b>Thread Series Designator:</b>	Unjf All Ends
<b>Specification/standard Data:</b>	96906-ms21900 Government Standard

## How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.