

Description

Outside diameter: 1/2", carbon steel, adapter flareless tube to flared tube, MS21900 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21900V8P](#)

SKU / Model:	MS219008
Minimum Qty (MOQ):	1
NSN:	4730-00-421-1353
Schedule B:	7326.90.8588
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21900-8 Specifications

Thread Class:	3a All Ends
End Item Identification:	Aircraft Application
Connection Style:	External Seat For Gasket Seal (boss) 2nd End
Connection Style:	Flared W/ Gasket Seal (boss) 1st End
Connection Type:	Threaded External Boss All Ends
Nominal Thread Size:	0.750 Inches All Ends
Nominal Overall Length:	1.469 Inches
Material:	Steel Comp 1137 Overall And Steel Comp 1141 Overall
Material Document And Classification:	Fed Std 66 Aisi/sae 1137 Or 1141 Fed Std All Material Responses Overall
Media For Which Designed:	Fluid Single Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Flared And Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21900 Government Standard

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.