

Description

outside: 3/16", adapter, flareless tube to flared tube, aluminum alloy 2024, MS21900 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21900D3
Minimum Qty (MOQ):	1
NSN:	4730-00-203-7461
Schedule B:	7609.00.0000
ECCN:	9A991
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS21900D3 Specifications

Thread Class:	3a All Ends
Connection Style:	External Seat For Gasket Seal (boss) 2nd End
Connection Style:	Flared W/ Gasket Seal (boss) 1st End
Connection Type:	Threaded External Boss All Ends
Nominal Thread Size:	0.375 Inches All Ends
Nominal Overall Length:	1.156 Inches
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-268,t6 Fed Spec Single Material Response Overall
Media For Which Designed:	Fluid Single Response
Surface Treatment:	Anodize Overall
Style Designator:	Flared And Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21900 Government Standard

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900D3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.