

Description

outside diameter: 3/8", adapter, flareless tube to flared tube, MS21900 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------|
| SKU / Model: | MS21900D6 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-00-640-5099 |
| ECCN: | EAR99 |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |



P/N MS21900D6 Specifications

| | |
|---|--|
| Thread Class: | 3a All Ends |
| Maximum Operating Temp: | 275.0 Deg Fahrenheit Single Response |
| Connection Style: | External Seat For Gasket Seal (boss) 2nd End |
| Connection Style: | Flared W/ Gasket Seal (boss) 1st End |
| Connection Type: | Threaded External Boss All Ends |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch Single Response |
| Nominal Thread Size: | 0.562 Inches All Ends |
| Nominal Overall Length: | 1.281 Inches |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-225/6 Temper T6,t62 Or T851 Fed Spec Single Material Response Overall |
| Media For Which Designed: | Hydraulic Fluid Single Response |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,type 2,class 1 Mil Spec Single Treatment Response Overall |
| Style Designator: | Flared And Flareless W/ Center Wrenching Facility |
| Thread Series Designator: | Unjf All Ends |
| Specification/standard Data: | 96906-ms21900 Government Standard |

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900D6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.