

Description

outside diameter: 1/4", adapter flareless tube to flared, corrosion resistant steel 304, MS21900 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21900J4
Minimum Qty (MOQ):	1
NSN:	4730-01-022-4442
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21900J4 Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	135.0 Deg Celsius Single Response
Connection Style:	External Seat For Gasket Seal (boss) 2nd End
Connection Style:	Flared W/ Gasket Seal (boss) 1st End
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.438 Inches All Ends
Nominal Overall Length:	1.187 Inches
Material:	Steel Comp 304 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Inside
Surface Treatment:	Passivate Outside
Surface Treatment Document And Classification:	Mil-f-14072,e300,ty 2 Mil Spec Single Treatment Response Outside
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Inside
Style Designator:	Flared And Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21900 Government Standard

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900J4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.