

**Description**

outside diameter: 1/4", adapter flareless tube to flared, corrosion resistant steel 304, MS21900 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21900J4
Minimum Qty (MOQ):	1
NSN:	4730-01-022-4442
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



## P/N MS21900J4 Specifications

<b>Thread Class:</b>	3a All Ends
<b>Maximum Operating Temp:</b>	135.0 Deg Celsius Single Response
<b>Connection Style:</b>	External Seat For Gasket Seal (boss) 2nd End
<b>Connection Style:</b>	Flared W/ Gasket Seal (boss) 1st End
<b>Connection Type:</b>	Threaded External Boss All Ends
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch Single Response
<b>Nominal Thread Size:</b>	0.438 Inches All Ends
<b>Nominal Overall Length:</b>	1.187 Inches
<b>Material:</b>	Steel Comp 304 Overall
<b>Material Document And Classification:</b>	Qq-s-763 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Inside
<b>Surface Treatment:</b>	Passivate Outside
<b>Surface Treatment Document And Classification:</b>	Mil-f-14072,e300,ty 2 Mil Spec Single Treatment Response Outside
<b>Surface Treatment Document And Classification:</b>	Mil-s-5002 Mil Spec Single Treatment Response Inside
<b>Style Designator:</b>	Flared And Flareless W/ Center Wrenching Facility
<b>Thread Series Designator:</b>	Unjf All Ends
<b>Specification/standard Data:</b>	96906-ms21900 Government Standard

## How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900J4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.