

Description

MS21900J6 Boss Nipple

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS21900J6 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-842-2265 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



NO IMAGE
AVAILABLE

P/N MS21900J6 Specifications

| | |
|---|--|
| Thread Class: | 3a All Ends |
| Maximum Operating Temp: | -65.0 Deg Fahrenheit 2nd Response |
| Maximum Operating Temp: | 275.0 Deg Fahrenheit 1st Response |
| Connection Style: | External Seat For Gasket Seal (boss) 2nd End |
| Connection Style: | Flared W/ Gasket Seal (boss) 1st End |
| Connection Type: | Threaded External Boss All Ends |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch Single Response |
| Nominal Thread Size: | 0.562 Inches All Ends |
| Nominal Overall Length: | 1.281 Inches |
| Material: | Steel Comp 304 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | 66,300 Series Fed Std Single Material Response Overall |
| Media For Which Designed: | Air 2nd Response |
| Media For Which Designed: | Gas 3rd Response |
| Media For Which Designed: | Hydraulic Fluid 1st Response |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Overall |
| Style Designator: | Flared And Flareless W/ Center Wrenching Facility |
| Thread Series Designator: | Unjf All Ends |
| Specification/standard Data: | 96906-ms21900 Government Standard |

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/fitting/MS21900J6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.