

Description

MS21900J6 Boss Nipple

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21900J6
Minimum Qty (MOQ):	1
NSN:	4730-00-842-2265
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21900J6 Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	-65.0 Deg Fahrenheit 2nd Response
Maximum Operating Temp:	275.0 Deg Fahrenheit 1st Response
Connection Style:	External Seat For Gasket Seal (boss) 2nd End
Connection Style:	Flared W/ Gasket Seal (boss) 1st End
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.562 Inches All Ends
Nominal Overall Length:	1.281 Inches
Material:	Steel Comp 304 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66,300 Series Fed Std Single Material Response Overall
Media For Which Designed:	Air 2nd Response
Media For Which Designed:	Gas 3rd Response
Media For Which Designed:	Hydraulic Fluid 1st Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Style Designator:	Flared And Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21900 Government Standard

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/fitting/MS21900J6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.