

Description

tube outside diameter: 3/8", adapter, flareless tube to flared tube, corrosion resistant steel, cadmium plated,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS21900-6](#)

SKU / Model:	MS21900V6P
Minimum Qty (MOQ):	1
NSN:	4730-01-542-5326
ECCN:	EAR99
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings



* See page 2 for technical characteristics

P/N MS21900V6P Specifications

Thread Class:	3a All Ends
Connection Style:	Flared (tube) 1st End
Connection Style:	Flareless (tube) 2nd End
Connection Type:	Threaded External Tube All Ends
Nominal Thread Size:	0.562 Inches All Ends
Seat Angle:	12.0 Degrees 2nd End
Seat Angle:	37.0 Degrees 1st End
Nominal Outside Diameter Tube Accommodated:	0.375 Inches All Ends
Nominal Overall Length:	1.281 Inches
Part Name Assigned By Controlling Agency:	Adapter, Flareless Tube To Flared Tube
Special Features:	Material Corrosion Resistant Steel (15-5ph) Cadmium Plated
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall
Style Designator:	Flared And Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	81343 - As21900 Professional/industrial Association Standard

How to Order

Order this tube nipple from our inventory online by visiting <https://military-fasteners.com/fittings/tube+nipples/MS21900V6P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.