

**Description**

tube outside diameter: 3/8", adapter, flareless tube to flared tube, corrosion resistant steel, cadmium plated,

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[MS21900-6](#)

SKU / Model:	MS21900V6P
Minimum Qty (MOQ):	1
NSN:	4730-01-542-5326
ECCN:	EAR99
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings

NO IMAGE  
AVAILABLE

## P/N MS21900V6P Specifications

<b>Thread Class:</b>	3a All Ends
<b>Connection Style:</b>	Flared (tube) 1st End
<b>Connection Style:</b>	Flareless (tube) 2nd End
<b>Connection Type:</b>	Threaded External Tube All Ends
<b>Nominal Thread Size:</b>	0.562 Inches All Ends
<b>Seat Angle:</b>	12.0 Degrees 2nd End
<b>Seat Angle:</b>	37.0 Degrees 1st End
<b>Nominal Outside Diameter Tube Accommodated:</b>	0.375 Inches All Ends
<b>Nominal Overall Length:</b>	1.281 Inches
<b>Part Name Assigned By Controlling Agency:</b>	Adapter, Flareless Tube To Flared Tube
<b>Special Features:</b>	Material Corrosion Resistant Steel (15-5ph) Cadmium Plated
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Style Designator:</b>	Flared And Flareless W/ Center Wrenching Facility
<b>Thread Series Designator:</b>	Unjf All Ends
<b>Specification/standard Data:</b>	81343 - As21900 Professional/Industrial Association Standard

## How to Order

Order this tube nipple from our inventory online by visiting <https://military-fasteners.com/fittings/tube+nipples/MS21900V6P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.