

Description

corrosion resistant steel (15-5ph), cadmium plated, tube outside 1/2", adapter flareless tube to flared tube

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21900-8](#)

SKU / Model:	MS21900V8P
Minimum Qty (MOQ):	1
NSN:	4730-01-542-5339
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti

NO IMAGE
AVAILABLE

P/N MS21900V8P Specifications

Thread Class:	3a All Ends
Connection Style:	Flared (tube) 1st End
Connection Style:	Flareless (tube) 2nd End
Connection Type:	Threaded External Tube All Ends
Nominal Thread Size:	0.750 Inches All Ends
Seat Angle:	12.0 Degrees 2nd End
Seat Angle:	37.0 Degrees 1st End
Nominal Outside Diameter Tube Accommodated:	0.500 Inches All Ends
Nominal Overall Length:	1.469 Inches
Part Name Assigned By Controlling Agency:	Adapter, Flareless Tube To Flaredtube
Special Features:	Material Corrosion Resistant Steel (15-5ph) Cadmium Plated
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall
Style Designator:	Flared And Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	81343 - As21900 Professional/Industrial Association Standard

How to Order

Order this tube nipple from our inventory online by visiting <https://military-fasteners.com/fittings/tube+nipples/MS21900V8P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.