

P/N MS21900V8P

Description

corrosion resistant steel (15-5ph), cadmium plated, tube outside 1/2", adapter flareless tube to flared tube

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS21900-8

SKU / Model: MS21900V8P

Minimum Qty (MOQ):

NSN: 4730-01-542-5339

ECCN: EAR99

National Motor Freight: 052190, Pipe, tubing, or Pipe Or Tubing Fitti



^{*} See page 2 for technical characteristics

P/N MS21900V8P Specifications

Thread Class:	3a All Ends
Connection Style:	Flared (tube) 1st End
Connection Style:	Flareless (tube) 2nd End
Connection Type:	Threaded External Tube All Ends
Nominal Thread Size:	0.750 Inches All Ends
Seat Angle:	12.0 Degrees 2nd End
Seat Angle:	37.0 Degrees 1st End
Nominal Outside Diameter Tube Accommodated:	0.500 Inches All Ends
Nominal Overall Length:	1.469 Inches
Part Name Assigned By Controlling Agency:	Adapter, Flareless Tube To Flaredtube
Special Features:	Material Corrosion Resistant Steel (15-5ph) Cadmium Plated
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall
Style Designator:	Flared And Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	81343 - As21900 Professional/industrial Association Standard

How to Order

Order this tube nipple from our inventory online by visiting https://military-fasteners.com/fittings/tube+nipples/MS21900V8P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.