

Description

aluminum alloy 7075, tube outside 5/16", adapter flareless tube to flared tube

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21900W5
Minimum Qty (MOQ):	1
NSN:	4730-00-602-9268
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS21900W5 Specifications

Thread Class:	3a All Ends
End Item Identification:	Aircraft Application
Connection Style:	External Seat For Gasket Seal (boss) 2nd End
Connection Style:	Flared W/ Gasket Seal (boss) 1st End
Connection Type:	Threaded External Boss All Ends
Nominal Thread Size:	0.500 Inches All Ends
Nominal Overall Length:	1.156 Inches
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/6,t6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Inside
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Outside
Style Designator:	Flared And Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21900 Government Standard And 81349-mil-f-18280 Government Specification

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900W5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.