

**Description**

aluminum alloy 7075, tube outside 5/16", adapter flareless tube to flared tube

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21900W5
Minimum Qty (MOQ):	1
NSN:	4730-00-602-9268
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum

NO IMAGE  
AVAILABLE

## P/N MS21900W5 Specifications

<b>Thread Class:</b>	3a All Ends
<b>End Item Identification:</b>	Aircraft Application
<b>Connection Style:</b>	External Seat For Gasket Seal (boss) 2nd End
<b>Connection Style:</b>	Flared W/ Gasket Seal (boss) 1st End
<b>Connection Type:</b>	Threaded External Boss All Ends
<b>Nominal Thread Size:</b>	0.500 Inches All Ends
<b>Nominal Overall Length:</b>	1.156 Inches
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Qq-a-225/6,t6 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Inside
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Outside
<b>Style Designator:</b>	Flared And Flareless W/ Center Wrenching Facility
<b>Thread Series Designator:</b>	Unjf All Ends
<b>Specification/standard Data:</b>	96906-ms21900 Government Standard And 81349-mil-f-18280 Government Specification

## How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900W5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.