

Description

tube outside: 1/2", aluminum alloy 7075, adapter flareless tube to flared tube, MS21900 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------|
| SKU / Model: | MS21900W8 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-289-4681 |
| Schedule B: | 7609.00.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |



* See page 2 for technical characteristics

P/N MS21900W8 Specifications

| | |
|---|--|
| Thread Class: | 2a All Ends |
| Connection Style: | External Seat For Gasket Seal (boss) 2nd End |
| Connection Style: | Flared W/ Gasket Seal (boss) 1st End |
| Connection Type: | Threaded External Boss All Ends |
| Nominal Thread Size: | 0.750 Inches All Ends |
| Nominal Overall Length: | 1.468 Inches |
| Material: | Aluminum Alloy 2024 Overall Or Aluminum Alloy 2014 Overall |
| Material Document And Classification: | Qq-a-225/6,t6 Fed Spec 1st Material Response Overall Or Qq-a-225/4,t6 Fed Spec 2nd Material Response Overall |
| Media For Which Designed: | Hydraulic Fluid Single Response |
| Surface Treatment: | Zinc Overall |
| Surface Treatment Document And Classification: | Qq-z-363 Fed Spec Single Treatment Response Overall |
| Style Designator: | Flared And Flareless W/ Center Wrenching Facility |
| Thread Series Designator: | Unjf All Ends |
| Specification/standard Data: | 96906-ms21900 Government Standard |

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900W8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.