

**Description**

tube outside: 1/2", aluminum alloy 7075, adapter flareless tube to flared tube, MS21900 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21900W8
Minimum Qty (MOQ):	1
NSN:	4730-00-289-4681
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



\* See page 2 for technical characteristics

## P/N MS21900W8 Specifications

<b>Thread Class:</b>	2a All Ends
<b>Connection Style:</b>	External Seat For Gasket Seal (boss) 2nd End
<b>Connection Style:</b>	Flared W/ Gasket Seal (boss) 1st End
<b>Connection Type:</b>	Threaded External Boss All Ends
<b>Nominal Thread Size:</b>	0.750 Inches All Ends
<b>Nominal Overall Length:</b>	1.468 Inches
<b>Material:</b>	Aluminum Alloy 2024 Overall Or Aluminum Alloy 2014 Overall
<b>Material Document And Classification:</b>	Qq-a-225/6,t6 Fed Spec 1st Material Response Overall Or Qq-a-225/4,t6 Fed Spec 2nd Material Response Overall
<b>Media For Which Designed:</b>	Hydraulic Fluid Single Response
<b>Surface Treatment:</b>	Zinc Overall
<b>Surface Treatment Document And Classification:</b>	Qq-z-363 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Flared And Flareless W/ Center Wrenching Facility
<b>Thread Series Designator:</b>	Unjf All Ends
<b>Specification/standard Data:</b>	96906-ms21900 Government Standard

## How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21900W8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.