

Description

outside: 3/8", union, flareless tube, Carbon steel, MS21902 series fitting (Old Revision)

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21902V6P](#)

SKU / Model:	MS219026
Minimum Qty (MOQ):	1
NSN:	4730-00-203-7491
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



P/N MS21902-6 Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	275.0 Deg Fahrenheit Single Response
Connection Style:	External Seat For Gasket Seal (boss) 1st End
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.562 Inches All Ends
Nominal Overall Length:	1.188 Inches
Special Features:	Grumman Aerospace Corp A10 Aircraft
Material:	Steel Comp 1137 Overall Or Steel Comp 1141 Overall
Material Document And Classification:	Qq-s-637 Fed Spec Single Material Response Overall Or Astm A576-67t Assn Std Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Style Designator:	Flareless (tube)
Style Designator:	Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21902 Government Standard

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21902-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.