

## P/N MS21902D2

### **Description**

outside 1/8", union, flareless, aluminum alloy 2024, MS21902 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS21902D2

Minimum Qty (MOQ):

NSN: 4730-00-684-3527

Schedule B: 7609.00.0000

ECCN: 9A991

National Motor Freight: 051400, Pipe Fittings Aluminum









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21902D2 Specifications

Thread Class:	3a All Ends
Connection Style:	External Seat For Gasket Seal (boss) All Ends
Leg Length:	0.375 Inches Nominal All Ends
Connection Type:	Threaded External Boss All Ends
Nominal Thread Size:	0.312 Inches All Ends
Nominal Overall Length:	1.062 Inches
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-268,t6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Inside
Surface Treatment:	Anodize Outside
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Inside
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Outside
Style Designator:	Flareless (tube)
Style Designator:	Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends

## **How to Order**

Order this boss nipple from our inventory online by visiting <a href="https://military-fasteners.com/fittings/boss+nipples/MS21902D2">https://military-fasteners.com/fittings/boss+nipples/MS21902D2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/fittings/boss+nipples/MS21902D2">https://military-fasteners.com/fittings/boss+nipples/MS21902D2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/fittings/boss+nipples/MS21902D2">https://military-fasteners.com/fittings/boss+nipples/MS21902D2</a> and selecting the quantity you want then