

Description

Tube outside 3/8", union, flareless tube, aluminum alloy, MS21902 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS21902W6](#)

SKU / Model:

MS21902D6

Minimum Qty (MOQ):

2

NSN:

4730-00-289-6089

Schedule B:

7609.00.0000

ECCN:

EAR99

National Motor Freight:

051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS21902D6 Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	-65.0 Deg Fahrenheit 2nd Response
Maximum Operating Temp:	275.0 Deg Fahrenheit 1st Response
Connection Style:	External Seat For Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.562 Inches All Ends
Nominal Overall Length:	1.188 Inches
Special Features:	Rumman Aerospace Inc Supports A10 Aircraft
Material:	Aluminum Alloy 2024 Overall Or Aluminum Alloy 2014 Overall
Material Document And Classification:	Qq-a-225/6,t6 Or T62 Or T851 Fed Spec 1st Material Response Overall Or Qq-a-225/4,t6 Fed Spec 2nd Material Response Overall
Media For Which Designed:	Hydraulic Fluid 1st Response
Media For Which Designed:	Oxygen, Gaseous 2nd Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 1,tan Mil Spec Single Treatment Response Overall
Style Designator:	Flareless (tube)
Style Designator:	Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21902 Government Standard

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21902D6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.