

**Description**

Tube outside 3/8", union, flareless tube, aluminum alloy, MS21902 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS21902W6](#)

|                         |                                |
|-------------------------|--------------------------------|
| SKU / Model:            | MS21902D6                      |
| Minimum Qty (MOQ):      | 2                              |
| NSN:                    | 4730-00-289-6089               |
| Schedule B:             | 7609.00.0000                   |
| ECCN:                   | EAR99                          |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |



\* See page 2 for technical characteristics

# P/N MS21902D6 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a All Ends   |
| <b>Maximum Operating Temp:</b>                        | -65.0 Deg Fahrenheit 2nd Response   |
| <b>Maximum Operating Temp:</b>                        | 275.0 Deg Fahrenheit 1st Response   |
| <b>Connection Style:</b>                              | External Seat For Gasket Seal (boss) All Ends   |
| <b>Connection Type:</b>                               | Threaded External Boss All Ends   |
| <b>Maximum Operating Pressure:</b>                    | 3000.0 Pounds Per Square Inch Single Response   |
| <b>Nominal Thread Size:</b>                           | 0.562 Inches All Ends   |
| <b>Nominal Overall Length:</b>                        | 1.188 Inches  |
| <b>Special Features:</b>                              | Rumman Aerospace Inc Supports A10 Aircraft  |
| <b>Material:</b>                                      | Aluminum Alloy 2024 Overall Or Aluminum Alloy 2014 Overall  |
| <b>Material Document And Classification:</b>          | Qq-a-225/6,t6 Or T62 Or T851 Fed Spec 1st Material Response Overall Or Qq-a-225/4,t6 Fed Spec 2nd Material Response Overall |
| <b>Media For Which Designed:</b>                      | Hydraulic Fluid 1st Response  |
| <b>Media For Which Designed:</b>                      | Oxygen, Gaseous 2nd Response  |
| <b>Surface Treatment:</b>                             | Anodize Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625,ty 2,cl 1,tan Mil Spec Single Treatment Response Overall   |
| <b>Style Designator:</b>                              | Flareless (tube)  |
| <b>Style Designator:</b>                              | Flareless W/ Center Wrenching Facility  |
| <b>Thread Series Designator:</b>                      | Unjf All Ends   |
| <b>Specification/standard Data:</b>                   | 96906-ms21902 Government Standard   |

## How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21902D6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.