

Description

Outside diameter: 5/8", corrosion resistant steel, union, flareless tube

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21902J10
Minimum Qty (MOQ):	1
NSN:	4730-00-825-9396
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21902J10 Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	275.0 Deg Fahrenheit Single Response
Connection Style:	External Seat For Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.875 Inches All Ends
Nominal Overall Length:	1.562 Inches
Material:	Steel Comp 304 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Style Designator:	Flareless (tube)
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21902 Government Standard

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21902J10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.