



Military-Fasteners.com

P/N MS21902J5

Description

tube outside diameter: 5/16", union, flareless, corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21902J5
Minimum Qty (MOQ):	1
NSN:	4730-01-047-8628
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21902J5 Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	-65.0 Deg Fahrenheit 1st Response
Maximum Operating Temp:	275.0 Deg Fahrenheit 2nd Response
Connection Style:	External Seat For Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.500 Inches All Ends
Nominal Overall Length:	1.062 Inches
Material:	Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Media For Which Designed:	Aeronautical Fluid Single Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Style Designator:	Flareless (tube)
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21902 Government Standard

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21902J5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.