



Military-Fasteners.com

P/N MS21902J8

Description

tube outside 1/2", union, corrosion resistant steel 304, flareless tube, MS21902 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[AS21902J8](#)

| | |
|-------------------------|---|
| SKU / Model: | MS21902J8 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-00-720-1587 |
| Schedule B: | 7307.22.1000 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



* See page 2 for technical characteristics

P/N MS21902J8 Specifications

| | |
|---|---|
| Thread Class: | 3a All Ends |
| Maximum Operating Temp: | 275.0 Deg Fahrenheit Single Response |
| Connection Style: | External Seat For Gasket Seal (boss) All Ends |
| Connection Type: | Threaded External Boss All Ends |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch Single Response |
| Nominal Thread Size: | 0.750 Inches All Ends |
| Nominal Overall Length: | 1.375 Inches |
| Material: | Steel Comp 304 Overall |
| Material Document And Classification: | Qq-s-763 Fed Spec Single Material Response Overall |
| Media For Which Designed: | Aeronautical Fluid Single Response |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Overall |
| Style Designator: | Flareless (tube) |
| Style Designator: | Flareless W/ Center Wrenching Facility |
| Thread Series Designator: | Unjf All Ends |
| Specification/standard Data: | 96906-ms21902 Government Standard |

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21902J8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.