

Description

corrosion resistant steel (316), tube outside 1/4", union, flareless tube

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21902K4
Minimum Qty (MOQ):	1
NSN:	4730-00-009-8259
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



P/N MS21902K4 Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	-65.0 Deg Fahrenheit 2nd Response
Maximum Operating Temp:	275.0 Deg Fahrenheit 1st Response
Connection Style:	External Seat For Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.438 Inches All Ends
Nominal Overall Length:	1.062 Inches
Material:	Steel Comp 316 Overall Or Steel Comp 304 Overall
Material Document And Classification:	66,300 Series Fed Std Single Material Response Overall
Media For Which Designed:	Air 2nd Response
Media For Which Designed:	Hydraulic Fluid 1st Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-f-14072,e300,ty 2 Mil Spec Single Treatment Response Outside
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Inside
Style Designator:	Flareless (tube)
Style Designator:	Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21902K4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.