

Description

Corrosion resistant steel (15-5ph), cadmium plated, tube outside 1/4", union, flareless tube, MS21902 series tube

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21902-4](#)

SKU / Model:	MS21902V4P
Minimum Qty (MOQ):	1
NSN:	4730-01-542-5455
ECCN:	EAR99
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings



* See page 2 for technical characteristics

P/N MS21902V4P Specifications

Thread Class:	3a All Ends
Connection Style:	Flareless (tube) All Ends
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.438 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.250 Inches All Ends
Nominal Overall Length:	1.063 Inches
Part Name Assigned By Controlling Agency:	Union, Flareless Tube
Special Features:	Material Corrosion Resistant Steel (15-5ph) Cadmium Plated
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall
Style Designator:	Flareless (tube)
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	81343 - As21902 Professional/industrial Association Standard

How to Order

Order this tube nipple from our inventory online by visiting <https://military-fasteners.com/fittings/tube+nipples/MS21902V4P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.