

Description

outside diameter: 5/8", aluminum alloy, union, flareless tube, MS21902W series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21902D10](#)

| | |
|-------------------------|--------------------------------|
| SKU / Model: | MS21902W10 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-451-6045 |
| Schedule B: | 7609.00.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |



* See page 2 for technical characteristics

P/N MS21902W10 Specifications

| | |
|---|--|
| Thread Class: | 3a All Ends |
| Maximum Operating Temp: | 135.0 Deg Celsius Single Response |
| Connection Style: | External Seat For Gasket Seal (boss) All Ends |
| Connection Type: | Threaded External Boss All Ends |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch Single Response |
| Nominal Thread Size: | 0.875 Inches All Ends |
| Nominal Overall Length: | 1.562 Inches |
| Material: | Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-225/9,t73 Fed Spec Single Material Response Overall |
| Media For Which Designed: | Fluid Single Response |
| Surface Treatment: | Anodize Inside |
| Surface Treatment: | Anodize Outside |
| Surface Treatment Document And Classification: | Mil-a-8625,ty2,cl 2 Mil Spec Single Treatment Response Inside |
| Surface Treatment Document And Classification: | Mil-a-8625,ty2,cl 2 Mil Spec Single Treatment Response Outside |
| Style Designator: | Flareless (tube) |
| Style Designator: | Flareless W/ Center Wrenching Facility |
| Thread Series Designator: | Unjf All Ends |
| Specification/standard Data: | 96906-ms21902 Government Standard |

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21902W10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.