



★ FASTENERS

Military-Fasteners.com

P/N MS21902W10

Description

outside diameter: 5/8", aluminum alloy, union, flareless tube, MS21902W series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS21902D10](#)

SKU / Model:	MS21902W10
Minimum Qty (MOQ):	1
NSN:	4730-00-451-6045
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS21902W10 Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	135.0 Deg Celsius Single Response
Connection Style:	External Seat For Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.875 Inches All Ends
Nominal Overall Length:	1.562 Inches
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9,t73 Fed Spec Single Material Response Overall
Media For Which Designed:	Fluid Single Response
Surface Treatment:	Anodize Inside
Surface Treatment:	Anodize Outside
Surface Treatment Document And Classification:	Mil-a-8625,ty2,cl 2 Mil Spec Single Treatment Response Inside
Surface Treatment Document And Classification:	Mil-a-8625,ty2,cl 2 Mil Spec Single Treatment Response Outside
Style Designator:	Flareless (tube)
Style Designator:	Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21902 Government Standard

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21902W10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.