

Description

aluminum alloy 7075, tube outside 5/16", union - flareless tube

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS21902D5](#)

SKU / Model:	MS21902W5
Minimum Qty (MOQ):	1
NSN:	4730-00-475-5732
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS21902W5 Specifications

Thread Class:	3a All Ends
Connection Style:	External Seat For Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.500 Inches All Ends
Nominal Overall Length:	1.062 Inches
Material:	Aluminum Alloy 7075 Overall
Media For Which Designed:	Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty2,cl 2 Mil Spec Single Treatment Response Inside
Surface Treatment Document And Classification:	Mil-a-8625,ty2,cl 2 Mil Spec Single Treatment Response Outside
Style Designator:	Flareless (tube)
Style Designator:	Flareless W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21902 Government Standard

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21902W5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.