

**Description**

aluminum alloy 7075, tube outside 5/16", union - flareless tube

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[MS21902D5](#)

SKU / Model:	MS21902W5
Minimum Qty (MOQ):	1
NSN:	4730-00-475-5732
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



## P/N MS21902W5 Specifications

<b>Thread Class:</b>	3a All Ends
<b>Connection Style:</b>	External Seat For Gasket Seal (boss) All Ends
<b>Connection Type:</b>	Threaded External Boss All Ends
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch Single Response
<b>Nominal Thread Size:</b>	0.500 Inches All Ends
<b>Nominal Overall Length:</b>	1.062 Inches
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Media For Which Designed:</b>	Fluid Single Response
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty2,cl 2 Mil Spec Single Treatment Response Inside
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty2,cl 2 Mil Spec Single Treatment Response Outside
<b>Style Designator:</b>	Flareless (tube)
<b>Style Designator:</b>	Flareless W/ Center Wrenching Facility
<b>Thread Series Designator:</b>	Unjf All Ends
<b>Specification/standard Data:</b>	96906-ms21902 Government Standard

## How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/MS21902W5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.