

# P/N MS21905D6

## **Description**

Thread Size: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

## **Additional Information**

#### **Alternate Part Numbers**

## MS21905W6

SKU / Model: MS21905D6

Minimum Qty (MOQ):

NSN: 4730-00-278-2434

ECCN: EAR99

National Motor Freight: 051400, Pipe Fittings Aluminum



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21905D6 Specifications

Thread Class:	3a All Ends
Connection Style:	Flareless (tube) 1st End
Connection Style:	Flareless (tube) 2nd End
Leg Length:	1.031 Inches Minimum All Ends And 1.078 Inches Maximum All Ends
Connection Type:	Threaded External Boss 3rd End
Connection Type:	Threaded External Tube 1st End
Connection Type:	Threaded External Tube 2nd End
Nominal Thread Size:	0.562 Inches All Ends
Seat Angle:	12.0 Degrees 1st End
Seat Angle:	12.0 Degrees 2nd End
Nominal Outside Diameter Tube Accommodated:	0.375 Inches 2nd End
Nominal Outside Diameter Tube Accommodated:	0.375 Inches 1st End
Material:	Aluminum Alloy 2014 Overall
Material Document And Classification:	Qq-a-367,t6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21905 Government Standard

## **How to Order**

Order this tube to boss tee from our inventory online by visiting <a href="https://military-fasteners.com/fittings/tube+to+boss+tees/MS21905D6">https://military-fasteners.com/fittings/tube+to+boss+tees/MS21905D6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/fittings/tube+to+boss+tees/MS21905D6">https://military-fasteners.com/fittings/tube+to+boss+tees/MS21905D6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/fittings/tube+to+boss+tees/MS21905D6">https://military-fasteners.com/fittings/tube+to+boss+tees/MS21905D6</a> and selecting the quantity