

Description

MS21905 series fitting

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21905J6
Minimum Qty (MOQ):	1
NSN:	4730-00-702-6299
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21905J6 Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	-40.0 Deg Fahrenheit 2nd Response
Maximum Operating Temp:	275.0 Deg Fahrenheit 1st Response
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.031 Inches Nominal All Ends
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.562 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.375 Inches All Ends
Material:	Steel Comp 304 Overall Or Steel Comp 316 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Media For Which Designed:	Aeronautical Fluid 1st Response
Media For Which Designed:	Oxygen, Gaseous 2nd Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec 1st Treatment Response Overall And Qq-p-35,ty 1 Fed Spec 2nd Treatment Response Overall
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21905 Government Standard

How to Order

Order this tube tee from our inventory online by visiting <https://military-fasteners.com/fittings/tube+tees/MS21905J6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.