

**Description**

Thread Size: 1/2", flareless, MS21905 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS21905D6](#)

SKU / Model:	MS21905W6
Minimum Qty (MOQ):	1
NSN:	4730-00-475-4627
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



\* See page 2 for technical characteristics

## P/N MS21905W6 Specifications

<b>Thread Class:</b>	3a All Ends
<b>Maximum Operating Temp:</b>	135.0 Deg Celsius Single Response
<b>Connection Style:</b>	Flareless (tube) All Ends
<b>Leg Length:</b>	1.031 Inches Nominal All Ends
<b>Connection Type:</b>	Threaded External Tube All Ends
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch Single Response
<b>Nominal Thread Size:</b>	0.562 Inches All Ends
<b>Seat Angle:</b>	12.0 Degrees All Ends
<b>Nominal Outside Diameter Tube Accommodated:</b>	0.375 Inches All Ends
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-367,t73 Fed Spec Single Material Response Overall
<b>Media For Which Designed:</b>	Aeronautical Fluid Single Response
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf All Ends

## How to Order

Order this tube tee from our inventory online by visiting <https://military-fasteners.com/fittings/tube+tees/MS21905W6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.