

Description

tube outside diameter: 3/8", elbow, aluminum alloy, bulkhead universal, flareless tube, MS21907 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS21907W6](#)

SKU / Model:	MS21907D6
Minimum Qty (MOQ):	1
NSN:	4730-00-278-8165
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS21907D6 Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	275.0 Deg Fahrenheit Single Response
Leg Length:	1.562 Inches Nominal 1st End
Leg Length:	0.812 Inches Nominal 2nd End
Connection Type:	Threaded External Tube 1st End
Connection Type:	Unthreaded External Hose 2nd End
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.562 Inches 1st End Bulkhead
Nominal Thread Size:	0.562 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.375 Inches 1st End
Special Features:	Used On Grumman Aircraft,model A10. Aluminum Alloy 7075 Overall
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-367,t6 Fed Spec Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 1 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf 1st End Bulkhead
Specification/standard Data:	81343-as21907 Professional/industrial Association Standard

How to Order

Order this tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/tube+elbows/MS21907D6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.