

Description

Thread Size: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS219084T
Minimum Qty (MOQ):	1 EA
NSN:	4730-01-289-0753
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti

NO IMAGE
AVAILABLE

P/N MS21908-4T Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	275.0 Deg Fahrenheit Single Response
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.500 Inches Nominal 1st End
Leg Length:	0.938 Inches Nominal 2nd End
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.438 Inches 1st End Bulkhead
Nominal Thread Size:	0.438 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.250 Inches All Ends
Material:	Titanium Alloy Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf 1st End Bulkhead
Specification/standard Data:	96906-ms21908-4t Government Standard

How to Order

Order this elbow from our inventory online by visiting <https://military-fasteners.com/fittings/tube+elbows/MS21908-4T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.